

JFX220-2515



The JFX220-2515 is a feature packed large-format UV-LED flatbed printer designed to bring advanced production capabilities to a more accessible platform. Built for sign, graphics, and specialty print providers, it combines increased productivity, simplified operation, and expanded application versatility in a flexible 4' x 8' class solution.

As the next generation of the JFX200 Series, the JFX220-2515 is designed to help shops produce more efficiently, broaden the range of work they can offer, and access higher-end workflow and application capabilities without stepping up to a higher production-class platform.

Specifications

NA Warranty	1 Year
--------------------	--------

LATAM Warranty	1 Year
-----------------------	--------

Heads	4
--------------	---

For best results, always use Mimaki original inks.

Head Type	On-demand piezo
Dropet Technology	Variable / Grayscale
Head Arrangement	4 Staggered
Print Resolution	300, 450, 600, 900, 1,200 dpi X 300, 600, 1,200 dpi
Minimum Dot Size	7pl
Head Gap	1.2 to 3mm
Max Media Width	JFX220-2515 98.43 in (2500.00 mm)
Max Media Length	1930
Max Media Thickness	4.00 in (101.60 mm)
Max Media Weight1	10 lb/ft2 (50kg/m2)
Max Printing Width	98.43 in (2500.00 mm)
Max Printing Length	1500
Vacuum Zones	2
Media Registration	In-table pop-up edge registration and variable placement pins
Lamp Type	UV-LED
Curing Units	2
Cooling	Air-cooled
ID-cut	Yes
Range accuracy	68 ° to 77 ° F (20 ° to 25 ° C)
PICT	Yes
Connection Interface	Ethernet 1000BASE-T
Dimensions	JFX220-2515: 173.23 in (4400.00 mm) X 99.21 in (2520.00 mm) X 58.66 in (1490.00 mm)
Weight	JFX220-2515 2028.60 lb (920.00 kg)
Required Power	2 lines - Single-phase AC200-240±10% 12A or less - Single-phase AC200-240±10% 10A or less
Power Consumption - Max	INLET1: 2.88kVA or less, INLET2: 2.33kVA or less
Temperature	68-86F (20-30C)
Humidity	35~65%RH(Non-condensing)
Max Printing Speed	sqft/hr (56.00 sqm/hr)

For best results, always use Mimaki original inks.

Machine Certifications	VCCI class A, FCC class A, ETL IEC 62368-1, CE Marking (EMC, Low voltage, Machinery directive, and RoHS), CB, REACH, RCM, KC, UKCA
Ink Type/Color	UV-LED ELS-120 CMYK, Lc, Lm, W, Cl PR-200 Primer ELH-100 Cl, W EFS-150 FP, FY

Please visit us at: <https://www.mimakiusa.com>

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications are subject to change without notice.

All specifications are subject to change; consult your authorized Mimaki representative for current information.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2026, Mimaki USA, Inc.

Rev. 10/19/26

For best results, always use Mimaki original inks.