Specification Sheet

# JV200-160B




The Mimaki JV200 Series of eco-solvent, roll-to-toll printers are affordable, entry-level models that can produce indoor and outdoor prints on a large selection of media including vehicle wraps, banners, wall murals and posters. They can be configured in 54 and 64-inch widths and offer either dual 4-color or 8-color inksets.

## Specifications

| | |
|---|---|
| **NA Warranty** | 3-Years Coverage - 1 Year Warranty, 2 Years Parts Plus+ |
| **LATAM Warranty** | 2-Years Coverage |
| **Heads** | 1 |
| **Head Type** | On-demand piezo |
| **Droplet Technology** | Variable / Grayscale |
| **Head Series** | 330 |
| **Head Arrangement** | Single |
| **Channels** | 8 |

*For best results, always use Mimaki original inks.*

| | |
|---|---|
| **Nozzles per Channel** | 400 |
| **Print Nozzles** | 1 head x 400 nozzles x 8 rows |
| **Print Resolution** | 1200 X 1200 |
| **Minimum Dot Size** | 3pl |
| **Head Gap** | Manual 0.5mm Adj.(1.5/2.0) |

| **Max Media Width** | **JV200-130** | **JV200-160** |
|---|---|---|
| | 53.98 in (1371.00 mm) | 63.78 in (1620.00 mm) |

| | |
|---|---|
| **Max Media Thickness** | 0.04 in (1.00 mm) |
| **Max Media Dia** | 7.09 in (180.00 mm) |
| **Max Media Weight1** | 25kg or less |
| **Max Media Weight2** | 45kg or less w. OPT-J0502 |
| **Media Cores** | 2 inch, 3 inch |
| **Max Printing Width** | 53.58 in (1361.00 mm) |
| **Color LCD Control Panel** | Yes |
| **Nozzle Check Unit (NCU)** | Yes |
| **Integrated Media Cutting** | Yes |
| **Media Heaters** | 3 - Pre, Print, Post |
| **ID-cut** | Yes |
| **RIP** | RasterLink7 |
| **Design** | Simple Create |
| **PICT** | Yes |
| **Mimaki Remote Access (MRA)** | Yes |
| **Connection Interface** | Ethernet 1000BASE-T, USB 2.0 Hi-speed |

| **Dimensions** | | |
|---|---|---|
| | **JV200-130:** | 99.21 in (2520.00 mm) X 29.45 in (748.00 mm) X 53.94 in (1370.00 mm) |
| | **JV200-160:** | 109.06 in (2770.00 mm) X 29.45 in (748.00 mm) X 53.94 in (1370.00 mm) |

| **Weight** | **JV200-130** | **JV200-160** |
|---|---|---|
| | 286.65 lb (130.00 kg) | 308.70 lb (140.00 kg) |

| | |
|---|---|
| **Required Power** | AC(100~120V / 200~240V±10%)×2 50/60Hz±1Hz |
| **Power Consumption - Max** | 1,320W x2 |

*For best results, always use Mimaki original inks.*

| | |
|---|---|
| **Power Consumption - Avg** | 1,000W or less |
| **Power Consumption - Sleep** | 4.5W or less |
| **Standby** | Not more than 45 dB |
| **Continuous Operation** | Not more than 59 dB |
| **Temperature** | 68-86F (20-30C) |
| **Guaranteed Acccuracy** | 68-77F (20-25C) |
| **Humidity** | 35~65%RH(Non-condensing) |
| **Dust Level** | Equivalent to general office |
| **Max Printing Speed** | 236.81 sqft/hr (22.00 sqm/hr) |
| **MPS Print Mode** | 4 Color 600x1200 4pass (160 Size) |
| **Machine Certifications** | VCCI class A, FCC class A, ETL IEC 62368-1,CE Marking (EMC, Low voltage, Machinery directive, and RoHS), CB, Energy Star, RCM, KC |
| **Ink Type/Color** | Eco-Solvent \| SS21 CMYK Lc, Lm, Lk, Or, W \| SS22 CMYK Lc, Lm, Lk, Or, W |

Please visit us at: https://www.mimakiusa.com

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications are subject to change without notice.

All specifications are subject to change; consult your authorized Mimaki representative for current information.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2026, Mimaki USA, Inc. Rev. 6/29/26

*For best results, always use Mimaki original inks.*